

# FRS 660-5 Fuel Recirculating System Specification Sheet

## Product Description:

The FRS 660-5 UL (*Single Tank Unit*) Fuel Recirculating System is **UL 508A Listed and Green Clean Certified**. It is designed to automatically circulate and clean fuel at 5 GPM for a single storage tank on a preprogrammed schedule.

The FRS 660-5 UL utilizes **RCI Technologies patented** fuel purification technology, which contains no filters or moving parts. It is used as primary fuel purification and removes 100% of all free water, including emulsified water and up to 98% of the normal solid or particulate contaminants found in fuel, including sludge and algae to approximately 10 microns.

The control system is housed in a **NEMA 4**, key lockable enclosure. The system consists of an RCI Universal Fuel Purifier, a continuous duty motor and fuel pump. The system is PLC controlled, with an Operator Interface Touch Panel that allows for system programming and alarm monitoring. Automatic controls are governed by a programmable 7 days, 24-hour real time clock with user definable start and run times. Four (4) relay alarm outputs include: pump failure, purifier high water level, system high pressure and fuel catch basin leak. Standard internal relays allow alarm status to be remotely.

FRS Systems are designed for use with all Class II or III combustible fuels having a flash point of 100° F or higher. Multiple tank operations are available.

## Standard Features:

### System:

- Listing: **UL 508A**
- Approx. shipping weight: 275 lbs
- Power Requirements: Standard: 115 or 230 VAC, 60Hz, 1Ph (*Please Specify*)

### Cabinet:

- Dimensions: 36" W x 36" H x 12" D
- Rating: **NEMA 4**
- Construction: Single Door, Heavy Duty Powder Coated Steel (*white*)
- Mounting: Suitable for floor or wall mounting (*Wall and Floor Mounting Tabs Included*)
- Security: Individually Keyed Lock
- Fuel Leak Basin w/ Drain: Integral
- Leak Float Switch: 1/8" Liquid Detection
- Pressure Switch: Factory set at 75 psi
- Plumbing and Wiring: Factory assembled and tested

### Controls

- System Controller: **UL 508A** Standard PLC
- Operator Interface: 6" Monochrome Touch Screen Panel
- System Data Display: Touch Screen Interface

### Location:

- |  |                                      |
|--|--------------------------------------|
| PLC Controller                                   | In <b>NEMA 4X</b> Poly Pro Enclosure |
| H/O/A Keyed Selector & Summary Light Combination | Exterior of Front Door               |
| Test Reset Alarm Button                          | Exterior of Front Door               |
| Audible Horn                                     | Exterior of Front Door               |



FRS 660-5 

*All RCI Systems are cycle and leak tested for a minimum of 2 hours prior to shipment.*

### Fuel Purifier:

- Model Number: FP 700 Fuel Purifier
- Normal Flow: 5 GPM
- Water Removal: 100%
- Decontamination Unit: BIO-MAG 1/2"
- Water Drain Valve: 1" Brass
- Particulate Removal:
  - Primary: 98% to approx. (*10 micron*)
  - Secondary: Provided by Engine Mfg (*5 micron*)
  - Final Removal: Provided by Engine Mfg (*2 micron*)

### Pump:

- Type: Positive Displacement Pump
- Product to pump: Diesel Fuel
- Pump Rate: 5 GPM
- Pump Housing: Aluminum
- Pump Gears: Steel

### Pump Motor:

- Horse Power: 1/3 H.P.
- Enclosure: TEFC
- Frame: 56C
- Duty: Continuous
- Type: Capacitor Start

### Plumbing:

- 2 pcs. Brass 1/2" Manual Ball Valves (*Fuel Line Input/Output*)
- 1 pc. 1/2" Y Strainer
- 1 pc. Brass 1/2" Check Valves
- 3 pcs. Brass 1/2" Unions

*NOTE: For options/upgrades, see Options List. Specifications subject to change without notice.*

462 Borrego Court, Suite D • San Dimas, California 91773  
 Phone: (800) 868-2088 • (909) 305-1241 • Fax: (909) 305-1245  
 www.rcitechnologies.com • email: info@rcitechnologies.com

